

TERAFIB PIGTAILS COLOR CODED 900µm

SM/MM Ordering Information / Information pour Commande



TP12SCUSMBB	12 Fiber Pigtailes SC/UPC Single Mode 900µm 3 Meters Blue Boots
TP06SCUSMBB	06 Fiber Pigtailes SC/UPC Single Mode 900µm 3 Meters Blue Boots
TP12SCASMGB	12 Fiber Pigtailes SC/APC Single Mode 900µm 3 Meters Green Boots
TP06SCASMGB	06 Fiber Pigtailes SC/APC Single Mode 900µm 3 Meters Green Boots
TP12FCUSMBB	12 Fiber Pigtailes FC/UPC Single Mode 900µm 3 Meters Blue Boots
TP06FCUSMBB	06 Fiber Pigtailes FC/UPC Single Mode 900µm 3 Meters Blue Boots
TP12FCASMGB	12 Fiber Pigtailes FC/APC Single Mode 900µm 3 Meters Green Boots
TP06FCASMGB	06 Fiber Pigtailes FC/APC Single Mode 900µm 3 Meters Green Boots
TP12STUSMBB	12 Fiber Pigtailes ST/UPC Single Mode 900µm 3 Meters Blue Boots
TP06STUSMBB	06 Fiber Pigtailes ST/UPC Single Mode 900µm 3 Meters Blue Boots
TP12STASMGB	12 Fiber Pigtailes ST/APC Single Mode 900µm 3 Meters Green Boots
TP06STASMGB	06 Fiber Pigtailes ST/APC Single Mode 900µm 3 Meters Green Boots
TP12LCUSMBB	12 Fiber Pigtailes LC/UPC Single Mode 900µm 3 Meters Blue Boots
TP06LCUSMBB	06 Fiber Pigtailes LC/UPC Single Mode 900µm 3 Meters Blue Boots
TP12LCASMGB	12 Fiber Pigtailes LC/APC Single Mode 900µm 3 Meters Green Boots
TP06LCASMGB	06 Fiber Pigtailes LC/APC Single Mode 900µm 3 Meters Green Boots
Multimode	
TP12LCOM1BKB	12 Fiber Pigtailes 900µm LC MM OM1 62.5µm 3 Meters Black Boots
TP12LCOM3BKB	12 Fiber Pigtailes 900µm LC MM OM3 50µm 3 Meters Black Boots
TP12SCOM4AQB	12 Fiber Pigtailes 900µm SC MM OM4 50µm 3 Meters Aqua Boots
TP12FCOM3AQB	12 Fiber Pigtailes 900µm FC MM OM3 50µm 3 Meters Aqua Boots
TP12STOM4AQB	12 Fiber Pigtailes 900µm ST MM OM4 50µm 3 Meters Aqua Boots



Product Information

Product Name	Pigtail	Fiber Model	Single mode	Back Reflection	UPC -55dB
Product Style	12 Core Fiber	Fiber Size	9/125µm	Back Reflection	APC -65dB
Optical Connector	SC,LC,ST,FC,E2000,MPO	Jacket Color	Yellow	Pigtails Length	3 Meters
Connector End Face	PC – UPC - APC	Jacket Diameter	900µm	Lengths Tolerance	+2.5/-0 inch
Work Environment	Standard Indoor	Jacket Material	PVC/LSZH	Insertion Loss UPC/APC	0.3dB (max)
Fiber Core	Corning® SMF28 Ultra	Operating Temperature	-25 to +70 degrees	Storage Temperature	-40 to +75 D Celsius
Multimode					
Fiber Type	Corning® ClearCurve® OM2, OM3, OM4	Insertion Loss 0.4dB (max)	Back Reflection - 25dB	Ferrule Protection	Plastic Cap
AVAILABILITY	OM1 62.5/125µm	OM2 50/125µm	OM3 50/125µm	OM4 50/125µm	OM5 50/125µm

New York-USA / Montréal- CANADA www.terafib.com www.terafib.ca / info@terafib.com

PHONE: 1-800-325-5477 / +1-514-325-5477 +1-315-325-5477



Terafib Rev- 04-06-2022

