

TERAFIB PATCH CORD SM/MM 1.6 & 3mm



Ordering Information / Information pour Commande

TS9STUSTUS1	Patch Cord 3mm SM 9/125µm SMF-28U ST/UPC to ST/UPC Simplex 1 Meter
TD9STASTAS1	Patch Cord 3mm SM 9/125µm SMF-28U ST/APC to ST/APC Duplex 1 Meter
TS9STUSTAS1	Patch Cord 3mm SM 9/125µm SMF-28U ST/UPC to ST/APC Simplex 1 Meter
TD9SCUSCUS1	Patch Cord 3mm SM 9/125µm SMF-28U SC/UPC to SC/UPC Duplex 1 Meter
TS9SCUSCAS1	Patch Cord 3mm SM 9/125µm SMF-28U SC/UPC to SC/APC Simplex 1 Meter
TS9SCASCAS1	Patch Cord 3mm SM 9/125µm SMF-28U SC/APC to SC/APC Simplex 1 Meter
TY9LCULCAS1	Patch Cord 1.6mm SM 9/125µm SMF-28U LC/UPC to LC/APC Simplex 1 Meter
TY9LCULCUS1	Patch Cord 1.6mm SM 9/125µm SMF-28U LC/UPC to LC/UPC Simplex 1 Meter
TY9LCULCAS1	Patch Cord 1.6mm SM 9/125µm SMF-28U LC/UPC to LC/APC Simplex 1 Meter
TS9FCAFCAS1	Patch Cord 3mm SM 9/125µm SMF-28U FC/APC to FC/APC Simplex 1 Meter
TS9FCUFCAS1	Patch Cord 3mm SM 9/125µm SMF-28U FC/UPC to FC/APC Simplex 1 Meter
TS9FCUFCUS1	Patch Cord 3mm SM 9/125µm SMF-28U FC/UPC to FC/UPC Simplex 1 Meter
TS9FCAFCAS1	Patch Cord 3mm SM 9/125µm SMF-28U FC/APC to FC/APC Simplex 1 Meter
TY9E2AE2AS1	Patch Cord 1.6mm SM 9/125µm SMF-28U E2000/E2000/APC Simplex 1 Meter
TY9MTRMTRS1	Patch Cord 1.6mm SM 9/125µm SMF-28 Ultra MTRJ/MTRJ Simplex 1 Meter
Multimode	
TSOM1LCLCS1	Patch Cord LC/LC 1.6mm MM OM1 62.5 Corning Clear-Curve Simplex 1 Meter
TDOM2SCSCS1	Patch Cord SC/SC 3mm MM OM2 50µm Corning Clear-Curve Duplex 1 Meter
TDOM3SCSCS1	Patch Cord SC/SC 3mm MM OM3 50µm Corning Clear-Curve Duplex 1 Meter
TSOM4SCSCS1	Patch Cord SC/SC 3mm MM OM4 50µm Corning Clear-Curve Simplex 1 Meter



Product Name	Patch Cord	Fiber Model	Single mode	Back Reflection	UPC -55dB
Product Style	12 Core Fiber	Fiber Size	9/125µm	Back Reflection	APC -65dB
Optical Connector	SC,LC,ST,FC,E2000,MPO	Jacket Color	Yellow	Pigtails Length	3 Meters
Connector End Face	PC - UPC - APC	Jacket Diameter	1.6mm / 3mm	Lengths Tolerance	+2.5/-0 inch
Work Environment	Standard Indoor	Jacket Material	PVC / LSZH	Insertion Loss UPC/APC	0.3dB (max)
Fiber Core	Corning® SMF28 Ultra	Operating Temperature	-25 to +70 degrees	Storage Temperature	-40 to +75 D Celsius

Multimode

Fiber Type	Corning® ClearCurve® OM1, OM2, OM3, OM4	Insertion Loss Loss 0.4dB (max)	Back Reflection -25dB	Ferrule Protection	Plastic Cap
-------------------	---	---	---------------------------------	---------------------------	-------------

New York-USA / Montréal- CANADA www.terafib.com www.terafib.ca / info@terafib.com

PHONE: 1-800-325-5477 / +1-514-325-5477 +1-315-325-5477



Terafib Rev- 04-06-2022

