

# Pretium® Connector Housing (PCH)

one rack unit, holds two CCH connector panels

CORNING

The rack-mount Pretium® connector housings (PCH) are available in 1U, 2U and 4U sizes and mount in 19-in racks or cabinets. Combined with the modules, panels, harnesses, trunks and jumpers, they provide a tip-to-tip solution for your fiber optic network.

## Features and Benefits

**Compatible with Plug & Play™ Systems modules**  
Designed to support Plug & Play Systems applications

**Splice in the housing**  
Saves rack space and the cost of the second housing

**Removable top (1U, 2U)**  
Maximizes ease of access

**Transparent front door (04U and 02U)**  
Permits viewing while protecting installed patch cords

**Large removable fiber guides in front**  
Effectively manage high patch cord densities



Part Number: PCH-01U

## Standards

<b>RoHS</b>	Free of hazardous substances according to RoHS 2011/65/EU
<b>UL-Listed</b>	United States and Canadian safety standards

## Specifications

General Specifications	
Application	Enterprise Networks, Data Center
Mounting Type	Rack 19-in, Rack 23-in
Product Type	Rack-Mountable Hardware

  

Design - Hardware	
Housing Type	PCH
Housing Color	Gray
Fiber Capacity	Up to 24 fibers installing FC/SC/ST® Compatible connectors, or up to 48 installing LC connectors

# Pretium® Connector Housing (PCH)

one rack unit, holds two CCH connector panels

CORNING

## Design - Hardware

Height Unit	1U
Locking Availability	Front or rear
Number of Panels per Housing	2
Panel or Module Type	CCH
Splice Tray Options	4 category 2R, 2 category 4R
Fiber Density per Unit	48

## Mechanical Characteristics

Dimensions (W x D x H)	432 mm x 406 mm x 44.45 mm (17 in x 16 in x 1.75 in)
------------------------	--

## Ordering Information

Part Number	PCH-01U
Product Description	Pretium® Connector Housing, 1 rack unit, holds two CCH connector panels
EAN Code	4056418191829

## Shipping Information

Units per Delivery	1/1
Packaging Dimensions (W x D x H)	615.9 mm x 508 mm x 120.7 mm (24.25 in x 20 in x 4.75 in)
Shipping Weight	5 kg (11 lb)
Package Contents	Housing; Installation Guide; 2 Blank Panels; unit ID label; port identification label for 2 panels; 2 #10-32 x .38 screws; 8 #10-32 x 50 screws; 4 #12-24 x 50 screws; 4 1/8 x 4-in tie wrap, white; 2 spiral wraps, 2 ft; central member strain-relief clamp kit; left bracket for mounting UCC clamp; right bracket for mounting UCC clamp; universal cable clamp (UCC) kit with 5 cable inserts; 2 #6-32, SS nylon self-locking hex nut



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING