

Terafib SMA905 & SMA906 Fiber Connector



Product Information

Parameter 1	Parameter 2	Parameter 3	Parameter 4
Back Reflection	-20dB	Temperature	≤0.2dB (-40+85 sustain 100 hours)
Insertion Loss	≤ 1.0 dB	Hole Tolerance	128um to 1000um: -5/+15um 1000um to 1050um: -10/+25um
Vibration	10-55 Hz	Matting Durability	1000 cycles
Stainless Ferrule	ID = 128um +4/-0	ID / OD Housing	Metal

FUTURE

- Precision Drilled Ferrules
- Cable Supported: 3.0mm
- Application: FTTH / Medical and More
- Fiber: Drilled up to 1500um

Terafib SMA905 and SMA906 Connectors are available in a wide variety of sizes from 128um to 1500um

Part Number	Description	MM	Boot Color
TD0128SMA905R	Tera SMA905 Connector S-Steel Ferrules HR Drilled 128um 3mm Black Boot	Yes	Black
TD0140SMA906R	Tera SMA906 Connector S-Steel Ferrules HR Drilled 140um 3mm Black Boot	Yes	Black
TD0160SMA905H	Tera SMA905 Connector S-Steel Ferrules HH Drilled 160um 3mm Black Boot	Yes	Black
TD1500SMA906H	Tera SMA906 Connector S-Steel Ferrules HH Drilled 1500um 3mm Black Boot	Yes	Black

New York-USA / Montréal- CANADA www.terafib.com www.terafib.ca / info@terafib.com

PHONE: 1-800-325-5477 / 1-514-325-5477 1-315-325-5477



Terafib Rev- 07-16-2022

